

**Safety data sheet**  
**according to UK REACH**

Printing date 09.12.2025

Version number: 1.14

Revision: 01.02.2025

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product HIGH BUILD GLOSS VARNISH**
- **Article number:** 6508
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture** Surface Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**  
WRIGHTS OF LYMM LIMITED  
Wright House,  
Crouchley Lane,  
Lymm,  
Cheshire,  
WA13 0AS  
UNITED KINGDOM  
TEL: +44 (0)1925 752226  
EMAIL: [info@wrightsoflymm.co.uk](mailto:info@wrightsoflymm.co.uk)
- **Further information obtainable from:** [www.wrightsoflymm.co.uk](http://www.wrightsoflymm.co.uk)
- **1.4 Emergency telephone number:** +44 (0)1925 752226 (business hours)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

|                   |                                                                      |
|-------------------|----------------------------------------------------------------------|
| Flam. Liq. 3      | H226 Flammable liquid and vapour.                                    |
| Skin Sens. 1      | H317 May cause an allergic skin reaction.                            |
| STOT SE 3         | H336 May cause drowsiness or dizziness.                              |
| STOT RE 1         | H372 Causes damage to organs through prolonged or repeated exposure. |
| Aquatic Chronic 2 | H411 Toxic to aquatic life with long lasting effects.                |

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02   GHS07   GHS08   GHS09

- **Signal word** Danger
- **Hazard statements**  
H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

# Safety data sheet according to UK REACH

Printing date 09.12.2025

Version number: 1.14

Revision: 01.02.2025

**Trade name: High Build Gloss Varnish**

(Contd. of page 1)

**· Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· 2.3 Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

**· 3.2 Chemical characterisation: Mixtures****· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

|                                                                 |                                                                                                                                                                                                          |         |
|-----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| EC number: 919-446-0<br>Reg.nr.: 01-2119458049-33-xxxx          | Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)<br>Flam. Liq. 3, H226<br>STOT RE 1, H372; Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>STOT SE 3, H336                         | 25-50%  |
| EC number: 918-668-5<br>Reg.nr.: 01-2119455851-35-xxxx          | Hydrocarbons, C9, aromatics<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>STOT SE 3, H335-H336                                                                                | 2.5-10% |
| EC number: 919-857-5<br>Reg.nr.: 01-2119463258-33-xxxx          | Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H336                                                                      | 2.5-10% |
| EC number: 927-344-2                                            | H y d r o c a r b o n s , C 9 - C 1 0 , n - alkanes, isoalkanes, cyclics, aromatics (2-25%)<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>Acute Tox. 4, H302; STOT SE 3, H336 | ≤ 2.5%  |
| CAS: 64742-48-9<br>EINECS: 265-150-3                            | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H336                                                                        | ≤ 2.5%  |
| CAS: 96-29-7<br>EINECS: 202-496-6<br>Reg.nr.: 01-2119539477-28  | 2-butanone oxime<br>Eye Dam. 1, H318<br>Acute Tox. 4, H312; Skin Sens. 1, H317                                                                                                                           | ≤ 2.5%  |
| CAS: 136-52-7<br>EINECS: 205-250-6<br>Reg.nr.: 01-2119524678-29 | cobalt bis(2-ethylhexanoate)<br>Repr. 1A, H360Fd<br>Aquatic Acute 1, H400<br>Eye Irrit. 2, H319; Skin Sens. 1A, H317<br>Aquatic Chronic 3, H412                                                          | ≤ 2.5%  |

(Contd. on page 3)

# Safety data sheet according to UK REACH

Printing date 09.12.2025

Version number: 1.14

Revision: 01.02.2025

Trade name: **High Build Gloss Varnish**

(Contd. of page 2)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.  
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**  
Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.  
Ensure good ventilation/extraction at the workplace.  
Prevent formation of aerosols.

(Contd. on page 4)

# Safety data sheet according to UK REACH

Printing date 09.12.2025

Version number: 1.14

Revision: 01.02.2025

**Trade name: High Build Gloss Varnish**

(Contd. of page 3)

**Hygiene measures:**

Wash hands before breaks and at the end of workday.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.

**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:**

Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

**8.1 Control parameters**

Additional information about design of technical facilities: No further data; see section 7.

**Ingredients with limit values that require monitoring at the workplace:****Hydrocarbons, C9, aromatics**OEL Long-term value: 100 mg/m<sup>3</sup>**Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**OEL Short-term value: 1200 mg/m<sup>3</sup>**96-29-7 2-butanone oxime**OEL Long-term value: 1 mg/m<sup>3</sup>, 0.3 ppm**136-52-7 cobalt bis(2-ethylhexanoate)**WEL Long-term value: 0.1 mg/m<sup>3</sup>  
as Co; Carc, Sen

Additional information: The lists valid during the making were used as basis.

**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

**Respiratory protection:** When spraying the product, use a respiratory protective device.**Protection of hands:**

Protective gloves

(Contd. on page 5)

GB

# Safety data sheet according to UK REACH

Printing date 09.12.2025

Version number: 1.14

Revision: 01.02.2025

Trade name: **High Build Gloss Varnish**

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

|                  |                 |
|------------------|-----------------|
| Form:            | Liquid          |
| Colour:          | Clear           |
| Odour:           | Characteristic  |
| Odour threshold: | Not determined. |

· **pH-value:** Not determined.· **Change in condition**

|                                          |               |
|------------------------------------------|---------------|
| Melting point/freezing point:            | Undetermined. |
| Initial boiling point and boiling range: | 135 °C        |

· **Flash point:** >30 °C· **Flammability** Flammable.· **Auto-ignition temperature:** >200 °C· **Decomposition temperature:** Not determined.· **Ignition temperature:** Product is not selfigniting.· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

|        |           |
|--------|-----------|
| Lower: | 0.6 Vol % |
| Upper: | 7.0 Vol % |

· **Vapour pressure:** Not determined.· **Density at 20 °C:** 0.914 g/cm<sup>3</sup>· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with water:**

NOT MISCIBLE

· **Partition coefficient: n-octanol/water:** Not determined.· **Viscosity:**

|                   |                 |
|-------------------|-----------------|
| Dynamic at 20 °C: | 230 mPas        |
| Kinematic:        | Not determined. |

· **Solvent content:**

Organic solvents: 42.1 %

Solids content: 50.8 %

· **9.2 Other information** No further relevant information available.

GB

(Contd. on page 6)

# Safety data sheet according to UK REACH

Printing date 09.12.2025

Version number: 1.14

Revision: 01.02.2025

Trade name: **High Build Gloss Varnish**

(Contd. of page 5)

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable under normal conditions
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
No dangerous decomposition products when stored and handled correctly

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
Causes damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
- Acute Fish toxicity  
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
LC50 9.22 mg/l  
Species: *Oncorhynchus mykiss* (rainbow trout)  
Exposure duration: 96 h
- Acute toxicity for daphnia  
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
EC50 6.14 mg/l  
Species: *Daphnia magna* (Water flea)  
Exposure duration: 48 h
- Acute toxicity for algae  
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
ErC50 2.9 mg/l  
Species: *Pseudokirchneriella subcapitata* (green algae)  
Exposure duration: 72 h
- Acute bacterial toxicity  
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
EC50 1 - 10 mg/l

(Contd. on page 7)

# Safety data sheet according to UK REACH

Printing date 09.12.2025

Version number: 1.14

Revision: 01.02.2025

**Trade name: High Build Gloss Varnish**

(Contd. of page 6)

**Ecotoxicology Assessment**

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.

· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Toxic for fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**· **ADR**

1263 PAINT, ENVIRONMENTALLY HAZARDOUS

· **IMDG**

PAINT, MARINE POLLUTANT

· **IATA**

PAINT

· **14.3 Transport hazard class(es)**· **ADR, IMDG**· **Class**

3 Flammable liquids.

· **Label**

3

· **IATA**· **Class**

3 Flammable liquids.

· **Label**

3

(Contd. on page 8)

# Safety data sheet according to UK REACH

Printing date 09.12.2025

Version number: 1.14

Revision: 01.02.2025

Trade name: **High Build Gloss Varnish**

(Contd. of page 7)

|                                                                                                                                                         |                                                                                                                                            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>                                                                                                 | <b>III</b>                                                                                                                                 |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b><br>· <b>Special marking (ADR):</b>                                                   | Product contains environmentally hazardous substances:<br>cobalt bis(2-ethylhexanoate)<br>Symbol (fish and tree)<br>Symbol (fish and tree) |
| · <b>14.6 Special precautions for user</b><br>· <b>Hazard identification number (Kemler code):</b><br>· <b>EMS Number:</b><br>· <b>Stowage Category</b> | Warning: Flammable liquids.<br>30<br>F-E, <u>S-E</u><br>A                                                                                  |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>                                                                        | Not applicable.                                                                                                                            |
| · <b>Transport/Additional information:</b>                                                                                                              |                                                                                                                                            |
| · <b>ADR</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Excepted quantities (EQ)</b>                                                                   | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml                     |
| · <b>Transport category</b><br>· <b>Tunnel restriction code</b>                                                                                         | 3<br>D/E                                                                                                                                   |
| · <b>IMDG</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Excepted quantities (EQ)</b>                                                                  | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml                     |
| · <b>UN "Model Regulation":</b>                                                                                                                         | UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS                                                                                           |

\*

## SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **MAK (German Maximum Workplace Concentration)**

100-41-4 ethylbenzene

3A

· **Poisons Act**· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category**

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

(Contd. on page 9)

GB

# Safety data sheet according to UK REACH

Printing date 09.12.2025

Version number: 1.14

Revision: 01.02.2025

**Trade name: High Build Gloss Varnish**

(Contd. of page 8)

· **National regulations:**· **Technical instructions (air):**

| Class | Share in % |
|-------|------------|
| I     | 0.3        |
| NK    | 42.1       |

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Full text of H-Statements referred to under sections 2 and 3:**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department: LABORATORY· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- ATE: Acute toxicity estimate values
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- Repr. 1A: Reproductive toxicity – Category 1A
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**